

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical Name: Graffiti Remover Aerosol

Product Number: 1081

Manufacturer Information: Sunrise Environmental Scientific

Remit: PO Box 10207 Reno, NV 89510

Physical: 1175 Industrial Way Sparks, NV 89431

Phone Number: 775-359-8494 or 800-648-1153

Pages: 3

Web: SUNRISENV.COM

Application: Graffiti Removal Compound

UN-Number: N/A

Emergency Phone No.

Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview:

Signal Word: DANGER

Keep out of reach of children.

Potential Health Effects:

Inhalation: Excessive inhalation of vapors may cause irritation of the respiratory tract, nausea, dizziness and/or headache.

Skin Contact: Prolonged contact may cause irritation and/or dryness of skin.

Ingestion: May cause serious health effects including vomiting, nausea and/or gastrointestinal irritation.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient:	CAS #	Component WT%	PEL	TLV	IDLH
*Trichloroethylene	79-07-6	5%≤25%	50 ppm	50 ppm	5,000 ppm
*2-Butoxyethanol	111-76-2	4%≤20%	25 ppm	25 ppm	N/A

Comments: No OSHA, PEL or TLV established for proprietary penetrating system.

4. FIRST AID MEASURES

Inhalation: If affected by vapors, move to a well ventilated area immediately. If breathing is difficult seek physician help.

Skin Contact: Flush with water, immediately remove all contaminated clothing.

Ingestion: Do not induce vomiting and seek physician care.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue for at least 15 minutes and seek physician help.

Additional Information: None

5. FIRE FIGHTING MEASURES

Flash Point: 68°F COC

Upper Flammable Limit (UEL): 36.0%

Lower Flammable Limit (LEL): 6.7%

Auto Ignition: N/D

Rate of Burning: N/D

General Fire Hazards: Aerosol can may explode and release flammable propellant.

Hazardous Combustion Product: May produce irritating fumes in fire.

Extinguishing Media: Foam, Co2 and/or dry chemicals.

Fire Fighting Equipment/Instructions: Use SCBA equipment.

NFPA Rating: (Flammability 3) (Health 2) (Reactivity 1)

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Eliminate all the ignition sources such as electrical, static, frictional sparks and pilot. Isolate the area.

Environmental Precautions: Isolate the spilled area. Prevent additional further leakage or spillage, if safe to do so.

Method for Cleanup & Containment: Wear appropriate protective equipment and clothing during the clean-up. Use non-combustible material like vermiculite, sand, clay or other absorbent material to absorb the spilled liquid.

Additional Information: Follow local and federal regulations with regard to chemical spills.

7. HANDLING AND STORAGE

Handling Procedure: Avoid breathing mist or vapors. Avoid prolonged contact with skin. Avoid contact with eye. Wear suitable PPE.

Wash hands thoroughly after handling the product.

Storage Procedures: Keep in a well-ventilated cool place, away from open flame, heat, reactive chemicals and/or other source of ignition.